



PG | GB2003 | 004384



The Patent Office Concept House Cardiff Road Newport South Wales

NP10 800 REC'D 0 4 DEC 2003

> **WIPO** PCT

PRIORITY

COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before reregistration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

istration under the Companies Act does not constitute a new legal entity but merely s the company to certain additional company law rules.

Signed

Dated 18 November 2003

BEST AVAILABLE COPY

An Executive Agency of the Department of Trade and Industry

6 1

Patents Form 1/77

Patents Act 1977 (Rule 16)

Request for grant of a patent
(See the notes on the back of this form. You can also get

(See the notes on the back of this form. You can also get a explanatory leaflet from the Patent Office to help you fill this form)

FICE Office

110CT02 E754924-15 000180 _P01/7700 6.00-0223608.1

The Patent Office

Cardiff Road Newport South Wales NP9 1RH

1. Your reference

ABC/21081

2. Patent application number (The Patent Office will fill in this part)

0223608.1

'10 OCT 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

No Climb Products Limited ...

Alston Works Alston Road

Barnet

Herts, EN5 4EL United Kingdom 6331 557001

If the applicant is a corporate body, give the country/state of its incorporation

Patents ADP number (if you know it)

4. Title of the invention

Generation of Carbon Monoxide for Testing CO Sensors, Detectors and Alarms

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

A A Thornton & Co 235 High Holborn London WC1V 7LE

75001

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number Country

Priority application number
(If you know it)

Date of filing (day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing (day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

this request: (Answer 188 ft.)

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body. See note (d)) .YES

Patents Form 1/77



Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

Claim (s)

Abstract

Drawing(s)

· 10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

> Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

10 October 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Andrew B Crawford - 020 7405 4044

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) . If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77



Generation of Carbon Monoxide for Testing CO Sensors, Detectors and Alarms

Background

Gas sensors that are sensitive to carbon monoxide (CO) are used in various types of alarm. The most common of these are used in installed or portable life safety alarms (industrial or residential) where elevated CO levels pose risk to health/life and in other alarms where the presence of CO is sought to be detected as indicative of other danger (e.g. fire). Examples range from gas-fired boilers, heating and cooking appliances, through personal alarms worn by workers in areas where dangerous levels of CO might be present in the atmosphere, to fire detection devices which may use CO sensors alone or in conjunction with other fire sensors such as heat and/or smoke sensors within a fire detector or system.

Certain types of CO sensors are prone to deteriorate over time, such that their performance can be effectively limited after only a few years of operation. The precise timing of their failure is not accurately predictable since it depends on factors such as the environment in which they are installed. To ensure that the sensor is operating correctly, it needs to be tested. In addition to this, CO sensors often need testing for other reasons, and the requirement to test is covered increasingly by national and international Standards.

In order to test the operation of such CO sensors, it is preferable to introduce small quantities of CO in the vicinity of the detector, at a concentration which is sufficient to activate the detector, but which, if released into the local environment is well within the safe human exposure limits. Existing methods

of achieving this include the breaking of a small glass vial containing CO, and a pressurised canister containing CO diluted with air or nitrogen for example. These methods can be inconvenient and do not lend themselves very well to repeated operation with a number of sensors. They may also constitute a hazard due to the pressurisation of the canister or the concentration of the gas. Whilst some CO sensors are cross-sensitive to other gases also, testing with a stimulus of CO gas overcomes any difficulty of knowing the levels of cross-sensitivity and its variation with time, temperature, etc.

There are various methods of producing CO on an industrial scale, but these either are not suited to scaling down, or involve the use of hazardous chemicals. The present invention relates to a low power method for small-scale production of CO which can be incorporated into a small portable device for the testing of sensors. It overcomes the need to store the CO gas, uses no toxic or hazardous chemicals, and does not involve high pressures. Furthermore, this method is controllable by electrical/electronic means.

The present invention provides apparatus for generating carbon monoxide comprising an enclosure having an inlet and an outlet at least one of which is provided with less restricting air flow from the inlet to the outlet, a container located within the enclosure arranged to receive carbon material in intimate contact with an electrical heating element, and means for causing air to move from the inlet to the outlet.

Preferably, the apparatus is battery powered and also the container may be readily replaced.

In order that the present invention be more readily understood, an embodiment thereof will now be described with regard to the accompanying drawing which show a side view of an embodiment of the present invention.

The invention is based on the principle of heating carbon within an enclosure with a restricted supply of air. This will form both carbon monoxide and carbon dioxide. At a temperature of 708°C and above the carbon dioxide will be reduced to carbon monoxide by the hot carbon. This process is used on a large scale for industrial production of carbon monoxide, but for this invention is utilised in a small low power / portable device. One embodiment of this is illustrated in Figure 1.

A heatproof tube 1, made of ceramic, silica glass or a mica composite, of typical dimensions 50 mm long and 6 mm diameter is filled with carbon granules 2. A wire heating element 3 is included along the centre of the tube. Metal end caps 4 keep the carbon granules 2 in the tube 1 and provide electrical terminations for the element 3. The end caps 4 have a number of small holes to allow the passage of air and other gases through the tube. The tube 1 is supported within an outer casing 6 of typical dimensions 70 x 25 x 25 mm., by airtight heat-insulating bulkheads 7. A controlled amount of air is blown through the tube 1 by the fan 5.

The mixture of gases produced emerges via the holes 8 in the casing 6. In use, the fan and heating element are powered for a short period of typically 20 seconds to allow the carbon to reach the temperature at which CO formation becomes spontaneous, and produce sufficient for testing the operation of a CO sensor. Control of the amount of CO produced can be by control of the current and its duration applied to the element, or could incorporate a separate reference sensor for more accurate control. The restricted air flow is controlled by the fan speed, size of the holes in the end caps 4 and the size of the carbon granules, and is maintained at a value that optimises the production of CO.

4

The overall small size and low power nature of the device means that it may be housed in a portable instrument and powered from batteries, allowing it to be carried to the sensor to be tested.

The casing 6 and its contents can be in the form of a replaceable cartridge, to enable the efficiency of the device to be maintained should the carbon become depleted after a period of use.

Key Features.

Heating of carbon in a restricted and/or controlled atmosphere on a small scale.

Low power consumption with respect to industrial CO generation permits application to a small/portable, preferably battery-powered device.

Replaceable cartridge.

Option of control of amount of CO using a built-in sensor.

Small, safe amounts of carbon monoxide.

No hazardous materials or potentially dangerous pressures.

CLAIMS:

- 1. Apparatus for generating carbon monoxide comprising an enclosure having an inlet and an outlet at least one of which is provided with less restricting air flow from the inlet to the outlet, a container located within the enclosure arranged to receive carbon material in intimate contact with an electrical heating element, and means for causing air to move from the inlet to the outlet.
- 2. Apparatus according to claim 1 and further comprising a portable power supply for the electrical heating element.
- 3. Apparatus according to claim 2, wherein the portable power supply is one or more batteries.
- 4. Apparatus according to claim 1, 2 or 3, wherein the means to cause the air to move as a fan.
- 5. Apparatus according to claim 2, and comprising means for controlling the amplitude or duration of the current supplied by power supply.
- 6. Apparatus according to any one of the preceding claims, wherein restricting means comprises a baffle member provided with one or more holes.
- 7. Apparatus according to claim 1, wherein the container is readily removable from the enclosure so as to enable replacement of the carbon material.

8. Apparatus for generating carbon monoxide substantially as hereinbefore described with reference to the accompanying drawing.